

## Flare 1599

---

### High Peak Power Eye-Safe LIDAR Source

The Flare is a high peak power pulsed, flash lamp pumped, eye-safe infrared laser developed specifically as a LIDAR source.

#### Features

- Eye-safe infrared output
- 10 MW peak pulse output power
- 7ns pulse width
- Articulated arm for simple integration into OEM products
- Near TEM<sub>00</sub> beam quality
- Closed circuit water cooling
- External computer control over the repetition rate via the built-in RS232 port

#### Applications

- Eye-safe LIDAR
- Laser Dermatology
- Internal medicine (Endoscopy, etc.)



# Specifications

Parameter	Flare 1599
Wavelength	1599 nm
Repetition Rate	Up to 30 Hz
Energy Output	Up to 70 mJ
Pulse-to-pulse stability	< 10 %
Pulse Duration	7 ns
Q-switch	Active
External control	Connector/pin for TTL trigger input
Electrical Service	208/220/240 VAC, 10 A
Laser head dimensions	870 x 205 x 310 mm <sup>3</sup>
Power Supply dimensions	662 x 282 x 508 mm <sup>3</sup>
Water Service	Closed loop water to air heat exchanger. No external water source required
Operating temperature and humidity	10-28° C; 10-90 %
Vibration, acceleration	Standard FedEx test

All Specifications Subject to Change without Notice

## Content and Delivery

The delivered laser consists of the following:

- Laser Head;
- Integrated Power/Cooling Unit;
- Connecting Cables;
- Manual; and
- Test Record.

## Warranty

6 months for parts and labor.

### **Passat USA**

720 N. Hammonds Ferry Rd.  
Linthicum, MD 21090, USA  
Tel : (410) 609-2006  
Fax : (360) 323-6971  
E-mail : [info@passatinc.com](mailto:info@passatinc.com)

### **Passat Canada**

116D Viceroy Rd. Unit 1-4  
Concord, ON L4K 2M4, Canada  
Tel : (905) 695-1088  
Fax : (866) 422-0959  
E-mail : [info@passatltd.com](mailto:info@passatltd.com)

[www.passatltd.com](http://www.passatltd.com)